


# Welding Hose


Gas Accessories

## Twin



I.D. (In.)	O.D. (In.)	No. of Spirals	Working Pressure
3/16	7/16	2	200
1/4	17/32	2	200
5/16	19/32	2	200
3/8	21/32	2	200

## Single Line



I.D. (In.)	O.D. (In.)	No. of Spirals	Working Pressure
3/16	7/16	2	200
1/4	19/32	4	200
5/16	21/32	4	200
3/8	23/32	4	200

### Twin - Grade R

Tube: EPDM  
 Reinforcement: Multi-spiral  
 Cover: EPDM **RED & GREEN (BLUE)**  
 Operating Temperature: -40°F to +212°F  
 Application: **RED; Acetylene use only**, and where cover must resist abrasion, weather and ozone.  
**GREEN; (OXYGEN TOLERANT)**



**PRECUT TWIN, GRADE R (with fittings)**

**BULK TWIN, GRADE R Price Per Foot**

I.D. (inch) x LGTH (Ft.)	FIT-TINGS	PART No.	PRICE EA	I.D. (Inch)	PART No.	*10-499 (FT.)	BULK REEL**
3/16 x 12.5	A B	R31612AB	\$26.75	3/16	TR316	\$0.92	\$0.74
3/16 x 12.5	B B	R31612BB	\$25.66	1/4	TR14	\$1.00	\$0.80
3/16 x 25	A B	R31625AB	\$34.52	5/16	TR516	\$1.58	\$1.28
3/16 x 25	B B	R31625BB	\$34.75	3/8	TR38	\$1.78	\$1.55
1/4 x 12.5	B B	R1412BB	\$21.50	*10ft. minimum charge.			
1/4 x 25	B B	R1425BB	\$25.50				
1/4 x 50	B B	R1450BB	\$45.50				
1/4 x 100	B B	R14100BB	\$84.95				

### Single Line - Grade R

Tube: EPDM  
 Reinforcement: Multi-spiral  
 Cover: EPDM **RED OR GREEN (BLUE)**  
 Operating Temperature: -40°F to +212°F  
 Application: **RED; Acetylene use only**, and where cover must resist abrasion, weather and ozone.  
**GREEN; (OXYGEN TOLERANT)**

**BULK SINGLE, GREEN & RED, GRADE R PRICE PER FOOT**

I.D. (Inch)	GREEN PART No.	*10-499 (FT.)	FULL REEL**	RED PART No.	*10-499 (FT.)	BULK REEL**
3/16	R316G	\$1.35	\$0.70	R316R	\$1.35	\$0.70
1/4	R14G	\$1.71	\$0.84	R14R	\$1.71	\$0.84
5/16	R516G	\$1.88	\$1.00	R516R	\$1.88	\$1.00
3/8	R38G	\$2.12	\$1.12	R38R	\$2.12	\$1.12

### Single Line - Grade T

Tube: CR  
 Reinforcement: Multi-spiral  
 Cover: CR **RED OR GREEN (BLUE)**  
 Operating Temperature: -40°F to +212°F  
 Application: **RED; For use with all fuel gases**, and where a flame and oil resistant cover is required.  
**GREEN; (OXYGEN TOLERANT)**

**BULK SINGLE, GREEN & RED, GRADE T, PRICE PER FOOT**

I.D. (Inch)	GREEN PART No.	*10-499 (FT.)	FULL REEL**	RED PART No.	*10-499 (FT.)	BULK REEL**
3/16	T316G	\$1.97	\$0.98	T316R	\$1.97	\$0.98
1/4	T14G	\$2.28	\$1.21	T14R	\$2.28	\$1.21
5/16	T516G	\$2.58	\$1.35	T516R	\$2.58	\$1.35
3/8	T38G	\$2.88	\$1.47	T38R	\$2.88	\$1.47

**PRECUT SINGLE, RED, GRADE T, PROPANE / MAPP® GAS (with fittings) TURBOTORCH®, HVAC**

3/16 I.D. x 12 ft, B B Female Fittings – Part No. H-12 Price **\$34.95 EA**

**PRECUT SINGLE, RED (ACETYLENE ONLY), GRADE R (with fittings)**

I.D. (inch) x LGTH (Ft)	FIT-TINGS	PART No.	PRICE EA
3/16 x 6	A A	HA3-6	\$17.95
3/16 x 12.5	A A	HA3-1212	\$33.00
3/16 x 25	A A	HA3-25	\$39.50

SINGLE PLY FABRIC  
 250 PSI Working Pressure

*NOTE: ONLY GRADE "T" HOSE CAN BE USED ON PROPANE (LPG) OR PROPANE BASED GAS & ACETYLENE*

**WARNING:** Although Twin & Single Line hoses are designed to withstand working pressures of 200 psi, the user is alerted against the use of acetylene at pressures above 15 psi. The use of Apache, Flamex, Mapi, Propane and Propylene at regulator settings above 40 psi may be hazardous. Refer to RMA Bulletin "Precautions in the use of Welding Hose" for further information.

To insure the integrity of the Welding Hose assembly, we recommend the use of 1" long ferrules. Welding Hose should be inspected regularly for cover cuts and wear. When Welding Hose is not in use, both gas and oxygen should be turned off at the tank and all lines should be bled at the torch end.

### Twin - Grade T

Tube: CR  
 Reinforcement: Multi-spiral  
 Cover: CR **RED & GREEN (BLUE)**  
 Operating Temperature: -40°F to +212°F  
 Application: **RED; For use with all fuel gases**, and where a flame and oil resistant cover is required.  
**GREEN; (OXYGEN TOLERANT)**

**PRECUT TWIN, GRADE T (with fittings)**

**BULK TWIN, GRADE T Price Per Foot**

I.D. (inch) x LGTH (Ft.)	FIT-TINGS	PART No.	PRICE EA	I.D. (Inch)	PART No.	*10-499 (FT.)	BULK REEL**
3/16 x 12.5	A B	T31612AB	\$31.68	3/16	TT316	\$1.58	\$1.41
3/16 x 12.5	B B	T31612BB	\$31.68	1/4	TT14	\$1.88	\$1.71
3/16 x 25	A B	T31625AB	\$54.25	5/16	TT516	\$2.50	\$2.07
3/16 x 25	B B	T31625BB	\$54.00	3/8	TT38	\$2.88	\$2.35
1/4 x 25	B B	T1425BB	\$42.50	*10ft. minimum charge.			
1/4 x 50	B B	T1450BB	\$68.75				
1/4 x 100	B B	T14100BB	\$125.00				
3/8 x 50	B B	T3850BB	\$99.95				
3/8 x 100	B B	T38100BB	\$242.78	*10ft. minimum charge.			

**\*\*ADD R TO THE END OF THE PART NUMBER FOR BULK REELS. BULK REEL HOSES RANGE FROM 500' TO 760' IN LENGTH WITH NOT MORE THAN TWO LENGTHS PER REEL. EXACT LENGTH WILL BE CONFIRMED PRIOR TO SHIPPING.**

For Engine and Lift Truck propane (LP) gas Hose, see Propane Gas Accessories.  
 For Inert Gas Hose, see MIG /TIG Accessories.  
 For Air Hose, see Air Tool Accessories.

### PROPANE HOSE - PRECUT SINGLE, BLACK LP Gas Only, with B Fittings

9/16 - 18 LH hose fittings.  
 Working pressure: 350 PSI  
 outside diameter: 9/16" Inside diameter: 1/4"



I.D. (inch) x LGTH (Ft.)	FIT-TINGS	PART No.	PRICE EA
1/4 x 6	B B	HEF-6	\$31.14
1/4 x 10	B B	HEF-10	\$45.42
1/4 x 12	B B	HEF-12	\$51.71
1/4 x 20	B B	HEF-20	\$78.42
1/4 x 35	B B	HEF-35	\$130.42
1/4 x 50	B B	HEF-50	\$182.42