



**FOR PRICE LISTING
GO TO PAGE 317**

PLASMA CUTTING

Replacement Parts

Suitable For

AIRCO®	Torch Model	Power Supply Model
	n/a	40 - 50

T-043 Retaining Cap
T-045 Nozzle, Hand
T-051 Swirl Ring
T-052 Electrode, Air
T-095 Torch Insulator
T-038 (T-3458) O-Ring
T-055 TMT 40, Hand Torch

Optimum Cutting Speed Air Plasma on Mild Steel 40 Amps

Thickness	Cutting Speed (IPM)
3/8	0
1/4	40
1/8	80
1/16	120
	160
	200

REQUIREMENTS:
Gas: Air, Nitrogen
Pressure: 60 psi
Flow: 4.0 scfm

Suitable For

BINZEL®	Torch Model	Power Supply Model
	PSB 30/30 HF	n/a

T-442 Retaining Cap
T-443 Nozzle, 1.0 mm
T-483 Nozzle, 1.2 mm
T-445 Insulator Sleeve
T-484 Plastic Sleeve
T-446 Spring
T-447 Electrode, 15.5 mm
T-485 Electrode, 15.0 mm
T-486 Electrode, 14.5 mm
T-024 Electrode
T-025 TMT 500 Torch

Suitable For

BINZEL®	Torch Model	Power Supply Model
	PSB 31/31 HF, KK	n/a

T-488 Nozzle, 1.0 mm (31/31 HF)
T-489 Nozzle, 1.2 mm (31/31 HF)
T-495 Nozzle, 1.0 mm (31 KK)
T-496 Nozzle, 1.2 mm (31 KK)
T-491 Electrode, 15.5 mm
T-492 Electrode, 16.0 mm
T-493 Electrode, 16.5 mm
T-487 Retaining Cap, (31/31 HF)
T-494 Retaining Cap, (31 KK)
T-490 Sleeve, (31/31 HF)
T-497 Sleeve, (31 KK)
T-446 Spring, (31/31 HF)
T-498 Spring, (31 KK)
PX51902 Spacer Spring (all)

Suitable For

BINZEL®	Torch Model	Power Supply Model
	PSB 60/80/121	n/a

T-448 Spacer Spring
T-449 Double Pointed Spacer
T-450 Spring Support
T-451 Nozzle, 1.0 mm 40 A
T-452 Nozzle, 1.3 mm 60 A
T-453 Nozzle, 1.5 mm 110 A
T-454 Nozzle, 1.8 mm 120 A
T-455 Nozzle, 1.0 mm, Conical
T-456 Nozzle, 1.3 mm, Conical
T-457 Nozzle, 1.5 mm, Conical
T-458 Nozzle, 1.8 mm, Conical
T-459 Electrode, Air
T-460 Electrode

ITEMS NOT SHOWN
T-461 Spacer
T-462 Standoff Support
T-463 Crown Standoff

Suitable For

AIRCO®	Torch Model	Power Supply Model
	PCT 50	n/a

T-289 Shield Cup
T-290 Shield Cup, XL
T-291 Tip, 30 Amp
T-292 Tip, XL
T-293 Swirl Baffle
T-294 Swirl Baffle, XL
T-295 Electrode
T-296 Electrode, XL
T-357 O-Ring
T-297 TMT-31 Hand Torch

Suitable For

AIRCO®	Torch Model	Power Supply Model
	PCT 500	n/a

T-014 Retaining Cap, Tapered
T-015 Retaining Cap, Flared
T-016 Nozzle, .166
T-017 Nozzle, .187
T-018 Nozzle, .220
T-019 Nozzle, .250
T-020 Swirl Ring, .120, .166, .187, CCW
T-021 Swirl Ring, .120, .166, .187
T-022 Swirl Ring, .220
T-023 Swirl Ring, .250
T-024 Electrode
T-025 TMT 500 Torch

Suitable For

CEBORA®	Torch Model	Power Supply Model
	HP 041	25/30/35
	HP 50, MP 50	PROF 50

T-388 Tip, (a.) (all)
T-1871 Tip, (a.) Long Life (HP 50, MP 50)
T-389 Tip, (b.) Conical, lo-amp (all)
T-390 Tip, (c.) Long (all)
T-2979 Tip, (c.) Long Life (HP 50, MP 50)
T-391 Tip, (d.) Long Conical (all)
T-387 Nozzle Retaining Cap (HP 041)
T-392 Swirl Ring (all)
T-393 Electrode (HP 041)
T-397 Electrode (HP 50, MP 50)
T-395 Torch Head (HP 041)
T-399 Torch Head (HP 50, MP 50)
T-396 Retaining Cap (HP 50, MP 50)
T-398 Long Electrode (HP 041)
T-399 Long Electrode (HP 50, MP 50)
PX51803 Buggy (HP 50, MP 50)