

COLD GALV THINNER

MATERIAL SAFETY DATA SHEET

01/11/00

MSDS PROVIDED BY:

STOODY INDUSTRIAL AND WELDING SUPPLY, INC.

3316 National Ave., San Diego, Ca. 92113

Phone: (619) 234-6750

MILITARY EMERGENCY RESPONSE NUMBER 1-800-851-8061

VERSION DATE 08/06/97 (REPRODUCED SIWS)

COLD GALV THINNER

SECTION 1**PRODUCT IDENTIFICATION**

COMPANY NAME WHO PROVIDED MSDS..... HARRIS WELCO. DIV. OF J.W. HARRIS CO., INC.
COMPANY ADDRESS..... 1051 YORK RD
KINGS MOUNTAIN, NC 28086
EMERGENCY PHONE NUMBER..... (800)-424-9300
MSDS VERSION NUMBER..... 2
TRADE NAME..... COLD GALV THINNER
HAZARD RATING (HMIS)..... HEALTH - 1, FLAMMABILITY - 3, REACTIVITY - 0
HMIS DESIGNATED KEY..... 4-SEVERE HAZARD 2-MODERATE HAZARD 0-MINIMAL HAZARD
3-SERIOUS HAZARD 1 - SLIGHT HAZARD

SECTION 2**HAZARDOUS COMPONENTS**

<u>MATERIAL</u>	<u>% BY WEIGHT</u>	<u>CAS NUMBER</u>	<u>OSHA PEL</u>	<u>ACGIH TLV (Mg/M3)</u>	<u>SEC 313</u>
XYLENE	100	1330-20-7		100 PPM	NA

SECTION 3**PHYSICAL PROPERTIES**

BOILING POINT..... IBP - FBP (280 - 283F) 137.9 - 139.8 C
MELTING POINT..... NA
VAPOR PRESSURE..... 25C
VAPOR DENSITY (AIR=1)..... 3.7
SOLUBILITY IN WATER..... NEGLIGIBLE
SPECIFIC GRAVITY..... 15.6 / 15.6C 0.87
EVAPORATION RATE..... 0.7
APPEARANCE AND ODOR..... WATER-WHITE COLOR. AROMATIC HYDROCARBON ODOR.

SECTION 4**FIRE AND EXPLOSION DATA**

FLASH POINT..... TAG CLOSED CUP 27C (80F)
EXRINGUISHING MEDIA..... FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG.
SPECIAL PROCEDURES..... USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS. COOL
EXPOSED CONTAINERS WITH WATER
UNUSUAL HAZARDS..... DO NOT STORE OR MIX WITH STRONG OXIDANTS. COMBUSTIBLE LIQUID.

SECTION 5**REACTIVITY DATA**

STABILITY..... STABLE
CONDITIONS TO AVOID..... NA
HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR
INCOMPATIBILITY..... STRONG OXIDANTS LIKE LIQUID CHLORINE AND CONCENTRATED OXYGEN.
HAZARDOUS DECOMPOSITION PRODUCTS..... CARBON MOXIDE IN THE CASE OF INCOMPLETE COMBUSTION.

SECTION 6**HEALTH HAZARD DATA**

ROUTES OF ENTRY..... INHALATION, SKIN CONTACT AND INGESTION.
HEALTH HAZARDS..... AVOID BREATHING VAPOR. INHALATION OF HIGH VAPOR CONCENTRATIONS
MAY HAVE RESULTS FROM DIZZINESS AND HEADACHES TO UNCINSCIOUSNESS
PROLONGED OR REPEATED LIQUID CONTACT WILL DRY AND DEFAT THE SKIN,
LEADING TO IRRITATION AND DERMATITIS.
CARCINOGENICITY..... NA
SIGNS & SYMPTOMS OF EXPOSURE..... SEE ABOVE
MEDICAL CONDITIONS FROM EXPOSURE..... SEE ABOVE
EMERGENCY & FIRST AID..... IF OVERCOME BY VAPOR, REMOVE FROM EXPOSURE IMMEDIATELY, CALL A
PHYSICIAN. IF BREATHING IS IRREGULAR OR STOPPED, START RESUCITATION,
ADMINSTER OXYGEN. IF SWALLOWED DO NOT INDUCE VOMITING - CALL A
PHYSICIAN. REMOVE CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP
AND WATER. FLUSH EYES WITH WATER
ADDITIONAL INFORMATION..... NA

SECTION 7**PRECAUTIONS FOR SAFF HANDLING AND USE**

SPILL AND LEAK PROCEDURES..... NA
WASTE AND DISPOSAL METHOD..... NA
HANDLING AND STORING PRECAUTIONS..... NA
OTHER PRECAUTIONS..... NA

SECTION 8**CONTROL MEASURES**

RESPIRATORY MEASURES..... NA
VENTILATION..... NA
PROTECTIVE GLOVES..... NA
EYE PROTECTION..... NA
OTHER PROTECTIVE EQUIPMENT..... NA
WORK/HYGIENIC PRACTICES..... NA

SECTION 9**DISCLAIMER**

THIS DATA IS BELIEVED TO BE ACCURATE. HARRIS WELCO MAKES NO WARRRANTY TO AND DISCLAIMS ALL LIABILITY FROM RELIANCE.

SECTION 10**ADDITIONAL INFORMATION**

NA = NOT APPLICABLE