

STOODY INDUSTRIAL AND WELDING SUPPLY, INC.**MATERIAL SAFETY DATA SHEET****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****PRODUCT NAME:** Hydrogen, compressed**CHEMICAL NAME:** Hydrogen**CHEMICAL FAMILY:** Flammable gas**FORMULA:** H₂**SYNONYMS:** None**NAME AND ADDRESS:**STOODY INDUSTRIAL AND WELDING SUPPLY, INC.
3316 National Avenue
San Diego, CA 92113**TELEPHONE:****Emergency Phone: (800) 633-8253 (24 hr.)**
Routine information call: (619) 234-6750
Weekdays 7:30 AM – 5:00 PM**[USE]:** Various.**2. COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT NAME /CAS NUMBER	PERCENTAGE	OSHA PEL	ACGIH TLV
Hydrogen/1333-74-0	>99%	None	Simple Asphyxiant

[LD₅₀]: None. **[LC₅₀]:** None.**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW:****DANGER!** Flammable, high pressure gas.
Can form explosive mixtures with air.
Burns with an invisible flame.**POTENTIAL HEALTH EFFECTS INFORMATION:****ROUTES OF EXPOSURE:****INHALATION:** Asphyxiant. It should be noted that before suffocation could occur, the lower flammability limit of hydrogen in air would be exceeded; possibly causing both an explosive and oxygen-deficient atmosphere. Exposure to moderate concentrations may cause dizziness, headache, nausea and unconsciousness. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning, and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death.**EYE CONTACT:** None.**SKIN CONTACT:** None.**[SKIN ABSORPTION]:** None.**[INGESTION]:** None.**CHRONIC EFFECTS:** None.**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:** None**OTHER EFFECTS OF OVEREXPOSURE:** None.**CARCINOGENICITY:** Hydrogen is not listed by NTP, OSHA or IARC.**4. FIRST AID MEASURES****INHALATION:** Persons suffering from lack of oxygen should be removed to fresh air. If victim is not breathing, administer artificial respiration. If breathing is difficult, administer oxygen. Obtain prompt medical attention.**EYE CONTACT:** None.**SKIN CONTACT:** None.**INGESTION:** None.**NOTES TO PHYSICIAN:** None.**5. FIRE FIGHTING MEASURES****FLASH POINT:** Flammable gas.**AUTOIGNITION:** 565.5° C (1050° F)**FLAMMABLE LIMITS IN AIR BY VOLUME:****LOWER:** 4%. **UPPER:** 74%.

STOODY INDUSTRIAL AND WELDING SUPPLY, INC.

EXTINGUISHING MEDIA: CO₂, dry chemical, water spray or fog for surrounding area. Do not extinguish until hydrogen source is shut off.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Evacuate all personnel from danger area. Immediately cool container with water spray from maximum distance, taking care not to extinguish flames. If flames are accidentally extinguished, explosive re-ignition may occur. Stop flow of gas if without risk while continuing cooling water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Burns with a pale blue, nearly invisible flame. Hydrogen is easily ignited with low ignition energy. Hydrogen is lighter than air and can accumulate in the upper sections of enclosed spaces. Pressure in a container can build up due to heat, and it may rupture if pressure relief devices should fail to function.

HAZARDOUS COMBUSTION PRODUCTS: None.

[SENSITIVITY TO STATIC DISCHARGE]: Ignitable by static electricity.

[SENSITIVITY TO MECHANICAL IMPACT]: None

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Evacuate immediate area. Eliminate any possible sources of ignition, and provide maximum explosion-proof ventilation. Shut off source of hydrogen, if possible. If leaking from cylinder, or valve, contact your supplier. The presence of a hydrogen flame can be detected by approaching cautiously with an outstretched straw broom to make the flame visible. Never enter a confined space or other area where the concentration is greater than 10% of the lower flammable limit which is 0.4%.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN STORAGE: Specific requirements are listed in NFPA 50A. Cylinder storage locations should be well-protected, well-ventilated, dry, and separated from combustible materials. Cylinders should never knowingly be allowed to reach a temperature exceeding 125° F (52° C). Cylinders of hydrogen should be separated from oxygen cylinders or other oxidizers by a minimum distance of 20 ft., or by a barrier of non-combustible material at least 5 ft. high having a fire resistance rating of at least ½ hour. Full and empty cylinders should be segregated. Use a first-in, first-out inventory system to prevent full containers from being stored for long periods of time.

Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling or being knocked over. Protect cylinders from physical damage; do not drag, roll, slide or drop. Use a suitable hand truck for cylinder movement. Post "No Smoking or Open Flames" signs in the storage areas. There should be no sources of ignition. All electrical equipment should be explosion proof in the storage and use areas. Storage areas must meet national electric codes for class 1 hazardous areas.

PRECAUTIONS TO BE TAKEN IN HANDLING: Do not "crack" hydrogen cylinder valve before connecting it, since self-ignition may occur. Hydrogen is the lightest gas known and may collect in the top of buildings with out proper ventilation. It may leak out of a system which is gas-tight for air or other gases. Leak check system with leak detection solution, never with flame. If user experiences difficulty operating cylinder valve, discontinue use and contact supplier. Never insert an object (e.g., wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Use an adjustable strap wrench to remove over-tight or rusted caps. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Non-sparking tools should be used. For additional precautions in using hydrogen see Section 16 - Other Information.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**ENGINEERING CONTROLS:**

VENTILATION: Provide natural or explosion-proof ventilation adequate to ensure hydrogen does not reach its lower explosive limit of 4%.

RESPIRATORY PROTECTION (SPECIFY TYPE):

General Use: None.

Emergency Use: Air supplied respirators are required in oxygen-deficient atmospheres, air purifying respirators will not function. Before entering area you must check for flammable or oxygen-deficient atmospheres.

PROTECTIVE GLOVES: Work gloves are recommended when handling cylinders.

EYE PROTECTION: Safety glasses are recommended when handling cylinders.

OTHER PROTECTIVE EQUIPMENT: Safety shoes are recommended when handling cylinders. Cotton clothing is recommended for use to prevent static electric buildup.

9. PHYSICAL AND CHEMICAL PROPERTIES

MOLECULAR WEIGHT: 2.016

BOILING POINT (1 ATM): -423.0° F (-252.8° C)

SPECIFIC GRAVITY (Air =1): At 32° F (0° C) and 1 atm: 0.06960

FREEZING POINT/MELTING POINT: At 1 atm: -434.55° F (-259.2° C)

VAPOR PRESSURE (AT 20° C): Not applicable

GAS DENSITY: At 70° F (21.1° C) and 1 atm: 0.00521 lb/ft³ (0.08342 kg/m³)

EVAPORATION RATE (Butyl Acetate=1): Not applicable.

SOLUBILITY IN WATER: Vol/Vol at 60° F (15.6° C): 0.019

STOODY INDUSTRIAL AND WELDING SUPPLY, INC.

EXPANSION RATIO: Not applicable. (gas)

[pH]: Not applicable

APPEARANCE, ODOR AND STATE: Colorless, odorless and tasteless gas at normal temperature and pressure.

[COEFFICIENT OF WATER/OIL DISTRIBUTION]: Not available

[ODOR THRESHOLD]: Not applicable (odorless)

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY (Materials to Avoid): Oxidizing agents. Some steels are susceptible to hydrogen embrittlement at high pressures and temperatures.

REACTIVITY:

A) **HAZARDOUS DECOMPOSITION PRODUCTS:** None

B) **HAZARDOUS POLYMERIZATION:** Will not occur.

11. TOXICOLOGICAL INFORMATION

Hydrogen is a simple asphyxiant.

[IRRITANCY OF MATERIAL]: None.

[SENSITIZATION TO MATERIAL]: None.

[REPRODUCTIVE EFFECTS]: None.

[TERATOGENICITY]: None.

[MUTAGENICITY]: None.

[SYNERGISTIC MATERIALS]: None

12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected. Hydrogen does not contain any Class I or Class II ozone depleting chemicals (40 CFR Part 82). Hydrogen is not listed as a marine pollutant by DOT (49 CFR Part 171).

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused product in the cylinder. Return to supplier for safe disposal.

Residual product within process system may be vented at a controlled rate, to the atmosphere through a vent stack that discharges to an elevated point. This vent stack should be in an isolated area away from ignition sources.

14. TRANSPORT INFORMATION

DOT/IMO SHIPPING NAME: Hydrogen, compressed

HAZARD CLASS: 2.1 (Flammable Gas)

IDENTIFICATION NUMBER: UN 1049

[PIN]: 1049

PRODUCT RQ: None

SHIPPING LABEL(s): Flammable gas.

PLACARD (When required): Flammable gas.

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards and should be discouraged.

15. REGULATORY INFORMATION

The following information concerns selected regulatory requirements potentially applicable to this product. Not all such requirements are identified. Users of this product are responsible for their own regulatory compliance on a federal, state [provincial], and local level.

U.S. FEDERAL REGULATIONS:**EPA - ENVIRONMENTAL PROTECTION AGENCY**

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (40 CFR Parts 117 and 302):

Reportable Quantity (RQ): None

SARA: Superfund Amendment and Reauthorization Act

SECTION 302/304: Requires emergency planning on threshold planning quantities (TPQ) and release reporting based on reportable quantities (RQ) of EPA's extremely hazardous substances (40 CFR Part 355).

Extremely Hazardous Substances: None

Threshold Planning Quantity (TPQ): None

SECTIONS 311/312: Require submission of material safety data sheets (MSDSs) and chemical inventory reporting with identification of EPA defined hazard classes (40 CFR Part 370). The hazard classes for this product are:

IMMEDIATE:

No

PRESSURE:

Yes

STOODY INDUSTRIAL AND WELDING SUPPLY, INC.

DELAYED: No REACTIVITY: No
FIRE: Yes

SECTION 313: Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Hydrogen does not require reporting under Section 313

40 CFR PART 68: Risk Management for Chemical Accidental Release. Requires the development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Hydrogen is listed as a regulated substance in quantities of 10,000 pounds (4553 kg) or greater.

TSCA: Toxic Substance Control Act: Hydrogen is listed on the TSCA inventory.

OSHA - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:

29 CFR 1910.119: Process Safety Management of Highly Hazardous Chemicals. Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals as listed in Appendix A.

Hydrogen is not listed in Appendix A as a highly hazardous chemical. However, any process that involves a flammable gas on site in one location, in quantities of 10,000 pounds (4,553 kg) or greater is covered under this regulation unless it is used as fuel.

[CANADIAN REGULATIONS:]

[Controlled Product Hazard Class A, B1. This MSDS has been prepared in compliance with Controlled Product Regulations.]

16. OTHER INFORMATION

SPECIAL PRECAUTIONS: Use piping and equipment adequately designed to withstand pressures to be encountered. Use a check valve or other protective apparatus in any line or piping from the cylinder to prevent reverse flow.

Shipment of compressed gas cylinders which have not been filled with the owner's consent is a violation of Federal law (49 CFR Part 173.301 (b)).

MIXTURES: When two or more gases or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

OTHER INFORMATION:**NFPA RATINGS:**

HEALTH:	= 0	HEALTH:	= 0
FLAMMABILITY:	= 4	FLAMMABILITY:	= 4
REACTIVITY:	= 0	REACTIVITY:	= 0
SPECIAL:	= SA (CGA recommends this to designate simple asphyxiant)		

HMIS RATINGS:**STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:**

THREADED:	0-3000 psig	CGA 350
	3001-5500 psig	CGA 695
	5501-7500 psig	CGA703
PIN INDEXED YOKE:		None

ULTRA HIGH INTEGRITY: 724

For information on hydrogen systems refer to NFPA 50A *Gaseous Hydrogen Systems at Customer Sites*.

[Use the proper CGA connections, DO NOT USE ADAPTERS]

Further information about hydrogen can be found in the following pamphlets published by: Compressed Gas Association Inc. (CGA), 1725 Jefferson Davis Highway, Suite 1004, Arlington, VA 22202-4102. Telephone: (703)412-0900.

G-5	<i>Hydrogen</i>
G-5.3	<i>Commodity Specification for Hydrogen</i>
P-1	<i>Safe Handling of Compressed Gases in Containers</i>
P-14	<i>Accident Prevention in Oxygen-rich and Oxygen-Deficient Atmospheres</i>
SB-2	<i>Oxygen-Deficient Atmospheres</i>

[PREPARED BY]: Compressed Gas Association
1725 Jefferson Davis Highway
Arlington, VA 22202-4102
703 - 412 - 0900

[REFORMATTED BY]: Stody Industrial and Welding Supply, Inc.