PORTABLE SPOT WELDERS & ACCESSORIES

These lightweight, air-cooled units are portable, easy to operate, and provide a quick and effective means for spot welding mild, galvanized or stainless materials. These units are an excellent choice for maintenance work, and for spot welding applications that require portability and lower amperage welding.





Portable Spot Welders Model HSW-15 & HSW-25

HSW-25

500442

Resistance Spot Welding (for Maintenance, Sheet Process:

Metal Work)

Tip Notes: One set of tips is supplied with each set of tongs Maximum welding capabilities are obtained with

minimum tong length. Tips & Tongs are not included

Tips are made of RWMA Class 2 alloy

FEATURES

- Accommodates a wide variety of tongs and tips
- Hand lever locks tongs firmly on material, ensures positive, accurate fit-up
- Quick and easy adjustment for material thickness
- Reversible for left- or right-hand operation
- Comes complete with Power Cord and Plug
- Includes standard 6 in (152.4 mm) tongs and standard tips



*Combined thickness uncoated mild steel using 6 In (152 mm) tongs)

HSW-15 Model 500440 Part Number (Order No.) Price Ea. \$499.00 Ea

Work Capacity*
Rated Output at 50% Duty Cycle
Rated Output with Standard Tongs

6 In (152 mm) tongs 12 In (305 mm) tongs 18 In (457mm) tongs

Max Open-Circuit Voltage Dimensions

Input50/60 Hz

\$599.90 Ea 110 VAC, 30 A 220 VAC. 30 A 1/8 In 3/16 In 2.5 KVA 1.5 KVA 5550 A. 6750 A 5800 A. 4500 A. 4850 A. 3600 A. 1.6 2.5 H: 6 In (152 mm) H: 6 In (152 mm)

W: 3-1/4 in (83 mm) W: 3-1/4 in (83 mm) D: 13 In (330 mm) D: 16 In (406 mm) 22 lb (10 kg) 30 lb (14 kg)

Net Weight:

PORTABLE SPOT WELDER TONGS & TIPS (ACCESSORIES)

TORTABLE OF OT WEEDER TORGO & THE O (ACCESSORIES)							
Tongs w/Tips		Tips					
3-1/2" In	Standard 6 in (#040197) 12 in (#040198) 18 in (#040199)	Standard Flat (#040211) (#040212)	Part No.	Price Set (Ea)			
3-1/2" In	MO Offset 6 in (#040200) 12 in (#040201) 18 in (#040202)	MO Offset (#040215)	040197 040198 040199 040200	\$68.80 \$69.90 \$79.90 \$95.50			
6-1/2" In	TT-6 12 in (#040203) 18 in (#040204)	Standard Flat (#040212)	040201 040202 040203 040204 040205	\$99.98 \$110.80 \$99.90 \$110.80 \$99.90			
9-1/2" In	TT-9 12 IN (#040205) 18 IN (#040206)	Standard Flat (#040211) (#040212)	040206 040207 040208 040209	\$110.80 \$89.99 \$112.80 \$121.70			
7-1/2" In	G7 8 in (#040207)	Standard Flat (#040211 (#040212)	040211 040212 040213 040214	\$12.50 \$13.50 \$39.90 \$39.90			
	FF 8 in (#040208)	FF (#040213)					
	FH 5 IN (#040209)	FH (#040214)					

SPOT WELDER TIP FILE

Part No. 2290 Price \$19.90 Ea



Specially designed to dress Spot Welder Tips. 8" in length with one concave cut side and the other side safe (uncut)



Pilot Bonding Brush

Carbon Steel Wire Spot facing tool to assure tight joints

opol facing tool to assure light joints					
Pilot	Part	Max Safe	Price		
Diameter	Number	Free Speed	Ea		
3/32"	23334	20,000	\$16.34		
1/8"	23335	20,000	\$16.34		
5/32"	23336	20,000	\$16.34		
3/16"	23337	20,000	\$16.34		
1/4"	23338	20,000	\$16.34		

All Brushes: 1/2" brush dia., .004 wire size, 1/4" shank, 1/8" trim length from ring.

EDI weld force gauges



ELECTRODE DRESSERS, INC., provider of high quality products to the welding industry, is proud to offer the E.D.I. line of weld tip force gauges. These gauges were designed to be easy to use as well as durable enough to withstand the most adverse plant conditions. If accuracy is of importance to your operation, look no further that the E.D.I. force gauges to provide you with excellent results in both accuracy and repeatability. Better settings make better welds. Know that your pressure settings are



Part No. WFG-2

STANDARD FEATURES • dual scale of 900 kilos / 2000 lbs. capacity

- 1.5% accuracy anywhere on the dial
- unique "accu-seal" piston to prevent leakage
- universal swivel for 360° rotation
- available as liquid fill for shock absorption Call For Price or with last readout needle
 - call for quote on other capacities



TIP DRESSER

To remove "mushroomed" effect

TIP EXTRACTOR **FOR MALE CAP ELECTRODES**

from spot welding tips and bring pointed tips back to approximately their original shape. This can be done on the job without removing

Part No. 0600-0135 \$69.20 Ea

SPOT WELD DRILL BIT

tip from holder.



You can remove a spot weld without having to access both sides of the panel. 1-1/4" long x5/16" diameter. Can be used in any drill with a 700 to 1800 rpm. Use of cutting oil will greatly increase the life of the tool. Titanium Coated and Carbon Nitrites -this exceptional coating is extremely hard, while offering you a very low coefficient of friction, so it runs cool. The purple color of this bit comes from the carbon nitrites process, which makes this bit last 4 to 5 times longer than a standard HSS bit.

#90151-TICN - Price \$35.50 a