

4FH - FLAME HARD TOOL STEEL
MATERIAL SAFETY DATA SHEET
MSDS PROVIDED BY:
STOODY INDUSTRIAL AND WELDING SUPPLY, INC.
3316 National Ave., San Diego, Ca. 92113
Phone: (619) 234-6750
MILITARY EMERGENCY RESPONSE NUMBER 1-800-851-8061

01/11/00

Version Date 01/03/96 (REPRODUCED SIWS)

4FH - FLAME HARD TOOL STEEL

SECTION 1					PRODUCT IDENTIFICATION			
COMPANY NAME WHO SENT MSDS.....					HARRIS WELCO, DIV. OF J.W. HARRIS CO., INC.			
COMPANY ADDRESS.....					1051 YORK ROAD			
EMERGENCY PHONE NUMBER					KINGS MOUNTAIN, NC 28086			
MSDS VERSION NUMBER.....					(800)-424-9300			
TRADE NAME					2			
HAZARD RATING (HMIS)					4FH - FLAME HARD TOOL STEEL			
HMIS DESIGNATION KEY					HEALTH – 3			
					FLAMMABILITY – 0			
					REACTIVITY – 0			
					OTHER – 0			
					4 – SEVERE HAZARD			
					3 – SERIOUS HAZARD			
					2 – MODERATE HAZARD			
					1 – SLIGHT HAZARD			
					0 – MINIMAL HAZARD			
SECTION 2					HAZARDOUS COMPONENTS			
<u>MATERIAL</u>			<u>% BY WEIGHT</u>		<u>CAS NUMBER</u>		<u>ACGIH TLV (Mg/M3)</u>	<u>SEC 313</u>
TITANIUM DIOXIDE			NA		1317-65-7	10		NA
CALCIUM CARBONATE			NA		1317-65-3	15		NA
CALCIUM FLOURIDE			NA		14542-24-5	2.5		NA
MOLYBDENUM			.15-.25		7439-98-7	10		NA
SILICON			.15 – .3		7440-21-3	5		NA
CHROMIUM			.8 – 1.1		7440-47-3	1		YES
MANGANESE			.4 – .6		7439-96-5	1		YES
VANADIUM			<.05		1314-62-1	0.05		YES
POTASSIUM SILICATE			NA		1312-62-1	0.05		NA
SECTION 3					PHYSICAL PROPERTIES			
BOILING POINT.....					NA			
MELTING POINT					NA			
VAPOR PRESSURE.....					NA			
VAPOR DENSITY (AIR = 1)					NA			
SOLUBILITY IN WATER.....					NA			
SPECIFIC GRAVITY					NA			
EVAPORATION RATE					NA			
APPEARANCE AND ODOR.....					SOLID ROD FLUX COATED			
SECTION 4					FIRE AND EXPLOSION DATA			
FLASH POINT					SEE AMERICAN NATIONAL STANDARD Z.49.1			
EXTINGUISHING MEDIA					SEE AMERICAN NATIONAL STANDARD Z.49.1			
SPECIAL PROCEDURES.....					SEE AMERICAN NATIONAL STANDARD Z.49.1			
UNUSUAL HAZARDS					NA			

4FH - FLAME HARD TOOL STEEL

MATERIAL SAFETY DATA SHEET

SECTION 5	REACTIVITY DATA
STABILITY.....	STABLE
CONDITIONS TO AVOID.....	NA
HAZARDOUS POLYMERIZATION	WILL NOT OCCUR
INCOMPATABILITY.....	NA
HAZARDOUS DECOMPOSITION PRODUCTS.....	NA
SECTION 6	HEALTH HAZARD DATA
ROUTES OF ENTRY	INHALATION
HEALTH HAZARDS	PULMONARY IRRITATION FROM DUST INHALATION
CARCINOGENICITY	THE STATE OF CALIFORNIA REQUIRES THE FOLLOWING INFORMATION WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.
SIGNS & SYMPTOMS OF EXPOSURE	OVEREXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS. NAUSEA, OR DRYNESS OR IRRITATION OF NOSE OR EYES.
MEDICAL CONDITIONS FROM EXPOSURE	COULD EFFECT PULMONARY FUNCTIONS.
EMERGENCY & FIRST AID.....	REMOVE TO FRESH AIR.
ADDITIONAL INFORMATION	NONE
SECTION 7	PRECAUTIONS FOR SAFE HANDLING AND USE
SPILL AND LEAK PROCEDURES.....	NA
WASTE AND DISPOSAL METHOD.....	FOLLOW FEDERAL, STATE, AND LOCAL REGULATIONS
HANDLING AND STORING PRECAUTIONS.....	NA
OTHER PRECAUTIONS.....	NORMAL HANDLING COLD. CAUTION WHEN HOT.
SECTION 8	CONTROL MEASURES
RESPIRATORY MEASURES	WELD FUME RESPIRATOR OR AIRLINES RESPIRATOR FOR CONFINED SPACES.
VENTILATION	IN SEMI-OPEN OR POOR VENTILATION SPACES USE LOCAL EXHAUST. MECHANICAL EXHAUST RECOMMENDED FOR POORLY NATURAL VENT SPACES.
PROTECTIVE GLOVES.....	WELDER'S GLOVES.
EYE PROTECTION	FACE SHIELD & SAFETY GLASS #12.
OTHER PROTECTIVE EQUIPMENT	WELDERS CLOTHING FOR PROTECTION AGAINST SPARKS AND HOT MATERIALS.
HYGIENIC PRACTICES.....	DISPOSE OF WELDING STUBS AND KEEP SAFETY LENS CLEAN. FOR MAXIMUM SAFETY: BE CERTIFIED FOR, AND WEAR A RESPIRATOR AT ALL TIMES WHEN WELDING OR BRAZING.
SECTION 9	DISCLAIMER
THIS DATA IS BELIEVED TO BE ACCURATE. HARRIS WELCO MAKES NO WARRANTY TO AND DISCLAIMS ALL LIABILITY FROM RELIANCE.	
SECTION 10	ADDITIONAL INFORMATION
NA = NOT APPLICABLE CARCINOGENICITY INFORMATION: CHROMIUM COMPOUNDS ARE REQUIRED BY OSHA TO BE CONSIDERED CARCINOGENIC.	