

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 04/10/2015
Revision date: 01/05/2016

Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Temperature indicator

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust, fume
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective gloves
P302+P352 - If on skin: Wash with plenty of water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a doctor if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

P405 - Store locked up
P501 - Dispose of contents/container to an authorised waste collection point

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

5.84 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
5.84 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
5.84 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
hymecromone	(CAS No) 90-33-5	85.26 : 344 °F 90.79 : 356 °F 82.99 : 363 °F	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
salicylanilide	(CAS No) 87-17-2	89.87 : 266 °F 82.65 : 269 °F	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
dilithium molybdate	(CAS No) 13568-40-6	30.9 : 750 °F, 752 °F 70.4 : 1300 °F, 1292 °F	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
butyl 4-hydroxybenzoate	(CAS No) 94-26-8	82.79 – 83.63 : 140 °F	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
benzil	(CAS No) 134-81-6	81.6 194 °F	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
potassium molybdate	(CAS No) 13446-49-6	21.21 : 750 °F, 752 °F	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Iron oxide red	(CAS No) 1309-37-1	1.69 : 266 °F 0.11 : 750 °F, 752 °F 0.01 : 1300 °F, 1292 °F	Aquatic Chronic 2, H411
lithium carbonate	(CAS No) 554-13-2	1.2 : 750 °F, 752 °F 0.71 : 1300 °F, 1292 °F	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand. Water spray.
Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No specific fire or explosion hazard. Burning produces irritating, toxic and noxious fumes.
Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Always approach spills or fires from upwind/uphill. Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Dust impervious gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Dust impervious gloves.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Avoid generating dust. Contain and collect as any solid.
Methods for cleaning up : Minimize generation of dust. On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing dust, fume. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.
Incompatible products : Strong oxidizers. Strong bases.
Prohibitions on mixed storage : Keep away from incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Temperature indicator.

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)		
ACGIH	Not applicable	
OSHA	Not applicable	
salicylanilide (87-17-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
Iron oxide red (1309-37-1)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	Remark (ACGIH)	Pneumoconiosis
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³ (Fer, trioxyde de, fumées et poussières (exprimée en Fe)) 10 mg/m ³ (Rouge)
hymecromone (90-33-5)		
ACGIH	Not applicable	
OSHA	Not applicable	
potassium molybdate (13446-49-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
dilithium molybdate (13568-40-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
lithium carbonate (554-13-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
butyl 4-hydroxybenzoate (94-26-8)		
ACGIH	Not applicable	
OSHA	Not applicable	
benzil (134-81-6)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear dust impervious gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from incompatible materials. Avoid creating or spreading dust.

10.5. Incompatible materials

Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

salicylanilide (87-17-2)	
LD50 oral rat	2400 mg/kg
ATE CLP (oral)	2400.000 mg/kg bodyweight
Iron oxide red (1309-37-1)	
LD50 oral rat	> 10000 mg/kg
hymecromone (90-33-5)	
LD50 oral rat	3850 mg/kg
ATE CLP (oral)	3850.000 mg/kg bodyweight
lithium carbonate (554-13-2)	
LD50 oral rat	525 mg/kg

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

lithium carbonate (554-13-2)	
LD50 dermal rabbit	> 3000 mg/kg
LC50 inhalation rat (mg/l)	> 2 mg/l/4h
ATE CLP (oral)	525.000 mg/kg bodyweight

butyl 4-hydroxybenzoate (94-26-8)	
LD50 oral rat	13200 mg/kg
ATE CLP (oral)	13200.000 mg/kg bodyweight

benzil (134-81-6)	
LD50 oral rat	> 3000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Iron oxide red (1309-37-1)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Not listed in carcinogenicity class

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Likely routes of exposure	: Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

Iron oxide red (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l

lithium carbonate (554-13-2)	
LC50 fish 1	30.3 mg/l 96 h
EC50 Daphnia 1	33.2 mg/l 48 h

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 14: Transport information

In accordance with DOT and TDG

Not considered a dangerous good for transport regulations

Proper Shipping Name (ADR) : Not applicable

Transport hazard class(es) (ADR) :

Transport by sea

Transport hazard class(es) (IMDG) :

Air transport

Transport hazard class(es) (IATA) :

SECTION 15: Regulatory information

15.1. US Federal regulations

salicylanilide (87-17-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Iron oxide red (1309-37-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

hymecromone (90-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

potassium molybdate (13446-49-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

dilithium molybdate (13568-40-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

lithium carbonate (554-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 313 - Emission Reporting 0 %

butyl 4-hydroxybenzoate (94-26-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

benzil (134-81-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

salicylanilide (87-17-2)

Listed on the Canadian DSL (Domestic Substances List) inventory

Iron oxide red (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List) inventory

hymecromone (90-33-5)

Listed on the Canadian DSL (Domestic Substances List) inventory

potassium molybdate (13446-49-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

dilithium molybdate (13568-40-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

lithium carbonate (554-13-2)

Listed on the Canadian DSL (Domestic Substances List) inventory

butyl 4-hydroxybenzoate (94-26-8)

Listed on the Canadian DSL (Domestic Substances List) inventory

benzil (134-81-6)

Listed on the Canadian DSL (Domestic Substances List) inventory

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

EU-Regulations

salicylanilide (87-17-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Iron oxide red (1309-37-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

hymecromone (90-33-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

potassium molybdate (13446-49-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

dilithium molybdate (13568-40-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

lithium carbonate (554-13-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

butyl 4-hydroxybenzoate (94-26-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

benzil (134-81-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS)

All ingredients are listed in the Toxic Substances Control Act (TSCA)

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL)

15.3. US State regulations

lithium carbonate (554-13-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

Iron oxide red (1309-37-1)

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List

lithium carbonate (554-13-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes

: Added. Product.

Tempilstik® 266 °F (130 °C), 269 °F (132 °C), 344 °F (173 °C), 356 °F (180 °C), 363 °F (184 °C), 750 °F (399 °C), 1300 °F (704 °C), 140 °F (60 °C), 194 °F (90 °C), 752 °F (400 °C), 1292 °F (700 °C)

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Data sources : ACGIH 2000.
Canadian Centre for Occupational Health and Safety. Accessed at:
http://www.ccohs.ca/oshanswers/legis/whmis_classifi.html.
ESIS (European chemical Substances Information System; accessed at:
<http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.
European Chemicals Agency (ECHA) Registered Substances list. Accessed at
<http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to
Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th
edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE
COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and
mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending
Regulation (EC) No 1907/2006.
TSCA Chemical Substance Inventory. Accessed at
<http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Abbreviations and acronyms : ACGIH (American Conference of Government Industrial Hygienists).
ATE: Acute Toxicity Estimate.
CAS (Chemical Abstracts Service) number.
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population.
OSHA: Occupational Safety & Health Administration.
STEL: Short Term Exposure Limits.
TSCA: Toxic Substances Control Act.
TWA: Time Weight Average.

Other information : None.

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual
injury even if no treatment is given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,
and not reactive with water.



Full text of H-statements:

H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H411	Toxic to aquatic life with long lasting effects

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product